

# DMW-Drainage Mesh Wells (WSO)-Specifications



DMW-Drainage Mesh Well straight connector Specifications

Mesh Well		ID*OD	Pitch	Length
Size	Code	±3.0%mm	±3.0%mm	m
<b>6"</b>	WSO-150A	148*165	14.0mm	5m
<b>8"</b>	WSO-200A	195*216	14.5mm	5m
<b>10"</b>	WSO-250A	239*267	14.5mm	5m
<b>12"</b>	WSO-300A	290*318	15.0mm	5m
<b>16"</b>	WSO-400A	390*420	15.5mm	5m

Connector		ID*OD	Pitch	Length
Size	Code	±3.0%mm	±3.0%mm	cm
<b>6"F</b>	WSF-150A	166.0x183.0	14.5mm	35cm
<b>8"F</b>	WSF-200A	217.0*240.0	14.5mm	40cm
<b>10"F</b>	WSF-250A	268.0*290.0	14.5mm	45cm
<b>12"F</b>	WSF-300A	320.0*342.0	15.0mm	50cm
<b>16"F</b>	WSF-400A	422.0*452.0	15.5mm	55cm



The sidewall openings are high-density mesh design

The sidewall has T-type thread design and high compressive resistance

Mesh Well sidewall is Anti-Clog and minimizes soil entry without extra filter material, such as non-woven fabric, gravel.

